# DM-2065

Woven Adhesive **Release Liner** 

## Single Coated Woven Fabric

#### CONTENTS

Face	Cotton/ viscose fabric	
Adhesive	Latex-free, medical rubber pressure-sensitive	
Backing	Silicone coated one-side, 54 lb basis weight	

#### FACE PROPERTIES

Basis Weight	270 g/m²

Typical substrate values of uncoated materials.

ADHESIVE PROPERTIE	Test method		
Peel Adhesion	>2000 g/in 2 mil PET	PSTC-1 HDPE Panels	
Thickness	4.5 mil		
Color	White		
Biocompatibility	Cytotoxicity	Pass	
Adhesive testing generated from a 2 mil PET lab standard			

Adhesive testing generated from a 2 mil PET lab standard. Product safety data sheets are contained on file by customer.

#### **PRODUCT DESCRIPTION**

DM-2065 is a beige elastic woven fabric tape. It is coated on one side with a latex-free medical rubberbased adhesive and supplied on a paper liner.

#### SPLICES

Splices on tape and liner are functional in that they are intended for continuous process conditions.

### STANDARD LABELING

Materials will have core labeling stating the part number, roll number, lot number, width, and linear feet per roll. Note: Any additional labeling requirements should be noted at time of order entry.

#### TRACEABILITY

Material traceability must comply with current Good Manufacturing Practice will contain a lot numbe production records. Ce accompany each shipm **STORAGE CONDITIONS** Product should be storn packaging at temperatu **ROLL DIMENSIONS** *small* **Length:** 600 linear fee Width: 58 inch max. **Core:** 3 inch inside co Manufacturing Practices. Each shipment of material will contain a lot number, which is traceable through production records. Certificate of Conformance will accompany each shipment.

Product should be stored in original protective packaging at temperatures between 50-80°F.

**ROLL DIMENSIONS** Smaller roll length by request. Length: 600 linear feet max. 3 inch inside diameter

