

DM-7200



Single Coated Metallized Polypropylene

CONTENTS

Face	Metallized/pearlized OPP film
Adhesive	Medical grade, pressure-sensitive rubber
Backing	Silicone coated one-side, 54 lb basis weight

FACE PROPERTIES		Test method
Thickness	1.1 mil	
Tensile Strength	MD 13130 psi CD 28806 psi	ASTM D-882

Typical substrate values of uncoated materials.

ADHESIVE PROPERTIES		Test method
Peel Adhesion	>1600 g/in	PSTC-1
Polyken Probe Tack	450 g/in ²	ASTM D-2979
Loop Tack	5500 g/in ²	PSTC-16
Thickness	1.1 mil	
Biocompatibility	Cytotoxicity Primary Dermal Buehler	Pass Pass Pass

Adhesive testing generated from a 2 mil PET lab standard.
Product safety data sheets are contained on file.

PRODUCT DESCRIPTION

DM-7200 is a white, pearlized OPP (oriented polypropylene) film, metallized on one side. It is coated on one side with a medical grade rubber-based adhesive and supplied on a paper liner.

SPICES

Splices on tape and liner are functional in that they are intended for continuous process conditions.

STANDARD LABELING

Materials will have core labeling stating the part number, roll number, lot number, width, and linear feet per roll. *Note: Any additional labeling requirements should be noted at time of order entry.*

TRACEABILITY

Material traceability must comply with current Good Manufacturing Practices. Each shipment of material will contain a lot number, which is traceable through production records. Certificate of Conformance will accompany each shipment.

STORAGE CONDITIONS

Product should be stored in original protective packaging at temperatures between 50-80°F.

ROLL DIMENSIONS Smaller roll length by request.

Length: 2000 linear feet max.

Width: 59 inch max.

Core: 3 inch inside diameter

